

ANNUAL VEHICLE INSPECTION REPORT

VEHICLE HISTORY RECORD

REPORT
NUMBER

FLEET UNIT NUMBER

67129242 PTL2244741

DATE

09/19/24

MOTOR CARRIER OPERATOR

Zig. Freight Inc dba Royal 3 Inc

INSPECTOR'S NAME (PRINT OR TYPE)

Jugoslav Kovacevic

ADDRESS

6850 W. 63rd St.

THIS INSPECTOR MEETS THE QUALIFICATION REQUIREMENTS IN SECTION 396.19.

☒ YES

CITY, STATE, ZIP CODE

Chicago, IL 60638

VEHICLE IDENTIFICATION (✓ AND COMPLETE) ☐ LIC. PLATE NO. ☒ VIN ☐ OTHER

3H3V532K4RS119296

VEHICLE TYPE ☐ TRACTOR ☒ TRAILER ☐ TRUCK ☐ BUS

INSPECTION AGENCY/LOCATION (OPTIONAL)

☐ (OTHER)

VEHICLE COMPONENTS INSPECTED

OK	NEEDS REPAIR	REPAIRED DATE	ITEM	OK	NEEDS REPAIR	REPAIRED DATE	ITEM	OK	NEEDS REPAIR	REPAIRED DATE	ITEM
✓			1. BRAKE SYSTEM	✓			6. SAFE LOADING	✓			12. WINDSHIELD GLAZING
✓			a. Service Brakes	✓			a. Vehicle parts, load, dunnage, spare tire, etc., secured.	✓			No cracks, discoloration, obstacles, etc. (see 393.60 for exceptions).
✓			b. Parking Brake System	✓			b. Front End Structure	✓			13. WINDSHIELD WIPERS
✓			c. Brake Drums or Rotors	✓			c. Intermodal Container Securement Devices	✓			No missing, damaged, or inoperable wipers.
✓			d. Brake Hose	✓			7. STEERING MECHANISM	✓			14. MOTORCOACH SEATS
✓			e. Brake Tubing	✓			a. Steering Wheel Free Play	✓			Seats securely fastened to the vehicle structure.
✓			f. Low Pressure Warning Device	✓			b. Steering Column	✓			15. REAR IMPACT GUARD
✓			g. Tractor Protection Valve	✓			c. Front Axle Beam/All Other Steering Components	✓			In place, securely attached, proper size, proper placement (see 393.86).
✓			h. Air Compressor	✓			d. Steering Gear Box	✓			16. OTHER
✓			i. Electric Brakes	✓			e. Pitman Arm				List any other condition(s) which may prevent safe operation of this vehicle.
✓			j. Hydraulic Brakes	✓			f. Power Steering				
✓			k. Vacuum Systems	✓			g. Ball and Socket Joints				
✓			l. Antilock Brake System	✓			h. Tie Rods and Drag Links				
✓			m. Automatic Brake Adjusters	✓			i. Nuts				
✓			2. COUPLING DEVICES	✓			j. Steering System				
✓			a. Fifth Wheels	✓			8. SUSPENSION				
✓			b. Pintle Hooks	✓			a. Axle Positioning Parts				
✓			c. Drawbar/Towbar Eye	✓			b. Spring Assembly				
✓			d. Drawbar/Towbar Tongue	✓			c. Torque, Radius or Tracking Components				
✓			e. Safety Devices	✓			9. FRAME				
✓			f. Saddle-Mounts	✓			a. Frame Members				
✓			3. EXHAUST SYSTEM	✓			b. Tire and Wheel Clearance				
✓			a. No leaks forward of/ directly below the driver/sleeper compartment.	✓			c. Adjustable Axle Assemblies (Sliding Subframes)				
✓			b. Bus: No leaking/ discharging in violation of standard.	✓			10. TIRES				
✓			c. Unlikely to burn, char, or damage the electrical wiring, fuel supply, or any combustible part of vehicle.	✓			a. Steer-Axle Tires				
✓			4. FUEL SYSTEM	✓			b. All Other Tires				
✓			a. No visible leak.	✓			c. Speed-Restricted Tires				
✓			b. Fuel Tank Filler Cap	✓			11. WHEELS AND RIMS				
✓			c. Fuel tank securely attached.	✓			a. Lock or Side Ring				
✓			5. LIGHTING DEVICES	✓			b. Wheels and Rims				
✓			All required lights/reflectors operable.	✓			c. Fasteners				
✓				✓			d. Welds				

INSTRUCTIONS: MARK COLUMN ENTRIES TO VERIFY INSPECTION: ✓ OK, X NEEDS REPAIR, NA IF ITEMS DO NOT APPLY, _____ REPAIRED DATE

CERTIFICATION: THIS VEHICLE HAS PASSED ALL THE INSPECTION ITEMS FOR THE ANNUAL VEHICLE INSPECTION IN ACCORDANCE WITH 49 CFR PART 396.

Part 396, Appendix A – Minimum Periodic Inspection Standards

A vehicle does not pass an inspection if it has one of the following defects or deficiencies:

- 1. *Brake System*
- a. *Service brakes* – (1) Absence of braking action on any axle required to have brakes upon application of the service brakes (such as missing brakes or brake shoes) failing to move upon application of a wedge, S-cant, cam, or disc brake).
- (2) Missing or broken mechanical components including: shoes, lining pads, springs, anchor pins, spiders, cambolts, push-rods, and air chamber mounting bolts.
- (3) Loose brake components including air chambers, spiders, and cam shaft support brackets.
- (Example: ruptured diaphragm, check chamber)
- (5) Readjustment limits: (a) The maximum pressure given in the tables below and at §393.47(e). Any brake stroke exceeding the readjustment limit will be rejected. Stroke must be measured with engine off and reservoir pressure of 80 to 90 psi with brakes fully applied.

CLAMP-TYPE BRAKE CHAMBERS

Type	Outside diameter	Stroke readjustment limit
Brake	Outside diameter	Stroke readjustment limit
6	4 1/8 in. (114 mm)	1 1/8 in. (28.3 mm)
12	5 1/8 in. (133 mm)	1 1/8 in. (28.3 mm)
19	6 1/8 in. (157 mm)	1 1/8 in. (28.3 mm)
20	6 1/8 in. (162 mm)	1 1/8 in. (28.3 mm)
24	7 1/8 in. (184 mm)	1 1/8 in. (28.3 mm)
36	9 1/8 in. (236 mm)	2 1/8 in. (55.5 mm)
36	9 1/8 in. (236 mm)	2 1/8 in. (55.5 mm)

BENDIX DD-3 BRAKE CHAMBERS

Type	Outside diameter	Stroke readjustment limit
ROTOCHAMBER™ TYPE BRAKE CHAMBERS		
G	9 1/8 in. (235 mm)	2 in. (50.8 mm)
F	11 in. (279 mm)	2 in. (50.8 mm)
E	12 in. (305 mm)	1 1/2 in. (38.1 mm)
D	13 in. (330 mm)	1 1/2 in. (38.1 mm)
C	15 in. (381 mm)	1 1/2 in. (38.1 mm)
B	17 in. (432 mm)	1 1/2 in. (38.1 mm)
A	19 in. (483 mm)	1 1/2 in. (38.1 mm)
	Stroke readjustment limit	
BOLT-1™ TYPE BRAKE CHAMBERS		
Type	Outside diameter	Stroke readjustment limit
30	9 1/8 in. (236 mm)	2 in. (50.8 mm)

BOLT-TYPE BRAKE CHAMBERS

(b) For actuator types not listed in these tables, the pushrod stroke must not be greater than 80 percent of the rated stroke marked on the actuator by the actuator manufacturer, or greater than the readjustment limit marked on the actuator by the actuator manufacturer, or the stroke of the actuator.	(c) Brake linings or pads.	(d) Linings or pads.
50	3 in. (76.2 mm)	3 in. (76.2 mm)
55	3 1/8 in. (82.5 mm)	3 1/8 in. (82.5 mm)
56	3 1/4 in. (86 mm)	3 1/4 in. (86 mm)
57	3 1/2 in. (89 mm)	3 1/2 in. (89 mm)
58	3 3/4 in. (93 mm)	3 3/4 in. (93 mm)
59	3 7/8 in. (98 mm)	3 7/8 in. (98 mm)
60	4 in. (101.6 mm)	4 in. (101.6 mm)
61	4 1/8 in. (106 mm)	4 1/8 in. (106 mm)
62	4 1/4 in. (110 mm)	4 1/4 in. (110 mm)
63	4 1/2 in. (114 mm)	4 1/2 in. (114 mm)
64	4 3/4 in. (118 mm)	4 3/4 in. (118 mm)
65	4 7/8 in. (123 mm)	4 7/8 in. (123 mm)
66	5 in. (127 mm)	5 in. (127 mm)
67	5 1/8 in. (132 mm)	5 1/8 in. (132 mm)
68	5 1/4 in. (136 mm)	5 1/4 in. (136 mm)
69	5 1/2 in. (140 mm)	5 1/2 in. (140 mm)
70	5 3/4 in. (144 mm)	5 3/4 in. (144 mm)
71	5 7/8 in. (148 mm)	5 7/8 in. (148 mm)
72	6 in. (152 mm)	6 in. (152 mm)
73	6 1/8 in. (157 mm)	6 1/8 in. (157 mm)
74	6 1/4 in. (161 mm)	6 1/4 in. (161 mm)
75	6 1/2 in. (165 mm)	6 1/2 in. (165 mm)
76	6 3/4 in. (169 mm)	6 3/4 in. (169 mm)
77	6 7/8 in. (174 mm)	6 7/8 in. (174 mm)
78	7 in. (177.8 mm)	7 in. (177.8 mm)
79	7 1/8 in. (182.5 mm)	7 1/8 in. (182.5 mm)
80	7 1/4 in. (186 mm)	7 1/4 in. (186 mm)
81	7 1/2 in. (190 mm)	7 1/2 in. (190 mm)
82	7 3/4 in. (194 mm)	7 3/4 in. (194 mm)
83	7 7/8 in. (199 mm)	7 7/8 in. (199 mm)
84	8 in. (203.2 mm)	8 in. (203.2 mm)
85	8 1/8 in. (207 mm)	8 1/8 in. (207 mm)
86	8 1/4 in. (211 mm)	8 1/4 in. (211 mm)
87	8 1/2 in. (214 mm)	8 1/2 in. (214 mm)
88	8 3/4 in. (218 mm)	8 3/4 in. (218 mm)
89	8 7/8 in. (223 mm)	8 7/8 in. (223 mm)
90	9 in. (228.6 mm)	9 in. (228.6 mm)
91	9 1/8 in. (233 mm)	9 1/8 in. (233 mm)
92	9 1/4 in. (236 mm)	9 1/4 in. (236 mm)
93	9 1/2 in. (240 mm)	9 1/2 in. (240 mm)
94	9 3/4 in. (244 mm)	9 3/4 in. (244 mm)
95	9 7/8 in. (249 mm)	9 7/8 in. (249 mm)
96	10 in. (254 mm)	10 in. (254 mm)
97	10 1/8 in. (259 mm)	10 1/8 in. (259 mm)
98	10 1/4 in. (263 mm)	10 1/4 in. (263 mm)
99	10 1/2 in. (266 mm)	10 1/2 in. (266 mm)
100	10 3/4 in. (270 mm)	10 3/4 in. (270 mm)
101	10 7/8 in. (275 mm)	10 7/8 in. (275 mm)
102	11 in. (279.4 mm)	11 in. (279.4 mm)
103	11 1/8 in. (284 mm)	11 1/8 in. (284 mm)
104	11 1/4 in. (287 mm)	11 1/4 in. (287 mm)
105	11 1/2 in. (291 mm)	11 1/2 in. (291 mm)
106	11 3/4 in. (295 mm)	11 3/4 in. (295 mm)
107	11 7/8 in. (300 mm)	11 7/8 in. (300 mm)
108	12 in. (304.8 mm)	12 in. (304.8 mm)
109	12 1/8 in. (310 mm)	12 1/8 in. (310 mm)
110	12 1/4 in. (313 mm)	12 1/4 in. (313 mm)
111	12 1/2 in. (317 mm)	12 1/2 in. (317 mm)
112	12 3/4 in. (321 mm)	12 3/4 in. (321 mm)
113	12 7/8 in. (326 mm)	12 7/8 in. (326 mm)
114	13 in. (330 mm)	13 in. (330 mm)
115	13 1/8 in. (335 mm)	13 1/8 in. (335 mm)
116	13 1/4 in. (338 mm)	13 1/4 in. (338 mm)
117	13 1/2 in. (342 mm)	13 1/2 in. (342 mm)
118	13 3/4 in. (346 mm)	13 3/4 in. (346 mm)
119	13 7/8 in. (351 mm)	13 7/8 in. (351 mm)
120	14 in. (354 mm)	14 in. (354 mm)
121	14 1/8 in. (359 mm)	14 1/8 in. (359 mm)
122	14 1/4 in. (362 mm)	14 1/4 in. (362 mm)
123	14 1/2 in. (366 mm)	14 1/2 in. (366 mm)
124	14 3/4 in. (370 mm)	14 3/4 in. (370 mm)
125	14 7/8 in. (375 mm)	14 7/8 in. (375 mm)
126	15 in. (381 mm)	15 in. (381 mm)
127	15 1/8 in. (386 mm)	15 1/8 in. (386 mm)
128	15 1/4 in. (389 mm)	15 1/4 in. (389 mm)
129	15 1/2 in. (393 mm)	15 1/2 in. (393 mm)
130	15 3/4 in. (397 mm)	15 3/4 in. (397 mm)
131	15 7/8 in. (402 mm)	15 7/8 in. (402 mm)
132	16 in. (406.4 mm)	16 in. (406.4 mm)
133	16 1/8 in. (411 mm)	16 1/8 in. (411 mm)
134	16 1/4 in. (414 mm)	16 1/4 in. (414 mm)
135	16 1/2 in. (418 mm)	16 1/2 in. (418 mm)
136	16 3/4 in. (422 mm)	16 3/4 in. (422 mm)
137	16 7/8 in. (427 mm)	16 7/8 in. (427 mm)
138	17 in. (431.8 mm)	17 in. (431.8 mm)
139	17 1/8 in. (436 mm)	17 1/8 in. (436 mm)
140	17 1/4 in. (439 mm)	17 1/4 in. (439 mm)
141	17 1/2 in. (443 mm)	17 1/2 in. (443 mm)
142	17 3/4 in. (447 mm)	17 3/4 in. (447 mm)
143	17 7/8 in. (452 mm)	17 7/8 in. (452 mm)
144	18 in. (457.2 mm)	18 in. (457.2 mm)
145	18 1/8 in. (462 mm)	18 1/8 in. (462 mm)
146	18 1/4 in. (465 mm)	18 1/4 in. (465 mm)
147	18 1/2 in. (468 mm)	18 1/2 in. (468 mm)
148	18 3/4 in. (472 mm)	18 3/4 in. (472 mm)
149	18 7/8 in. (477 mm)	18 7/8 in. (477 mm)
150	19 in. (481.6 mm)	19 in. (481.6 mm)
151	19 1/8 in. (486 mm)	19 1/8 in. (486 mm)
152	19 1/4 in. (489 mm)	19 1/4 in. (489 mm)
153	19 1/2 in. (493 mm)	19 1/2 in. (493 mm)
154	19 3/4 in. (497 mm)	19 3/4 in. (497 mm)
155	19 7/8 in. (502 mm)	19 7/8 in. (502 mm)
156	20 in. (508 mm)	20 in. (508 mm)
157	20 1/8 in. (513 mm)	20 1/8 in. (513 mm)
158	20 1/4 in. (516 mm)	20 1/4 in. (516 mm)
159	20 1/2 in. (520 mm)	20 1/2 in. (520 mm)
160	20 3/4 in. (524 mm)	20 3/4 in. (524 mm)
161	20 7/8 in. (529 mm)	20 7/8 in. (529 mm)
162	21 in. (533.4 mm)	21 in. (533.4 mm)
163	21 1/8 in. (538 mm)	21 1/8 in. (538 mm)
164	21 1/4 in. (541 mm)	21 1/4 in. (541 mm)
165	21 1/2 in. (545 mm)	21 1/2 in. (545 mm)
166	21 3/4 in. (549 mm)	21 3/4 in. (549 mm)
167	21 7/8 in. (554 mm)	21 7/8 in. (554 mm)
168	22 in. (558.8 mm)	22 in. (558.8 mm)
169	22 1/8 in. (563 mm)	22 1/8 in. (563 mm)
170	22 1/4 in. (566 mm)	22 1/4 in. (566 mm)
171	22 1/2 in. (570 mm)	22 1/2 in. (570 mm)
172	22 3/4 in. (574 mm)	22 3/4 in. (574 mm)
173	22 7/8 in. (579 mm)	22 7/8 in. (579 mm)
174	23 in. (584.2 mm)	23 in. (584.2 mm)
175	23 1/8 in. (589 mm)	23 1/8 in. (589 mm)
176	23 1/4 in. (592 mm)	23 1/4 in. (592 mm)
177	23 1/2 in. (596 mm)	23 1/2 in. (596 mm)
178	23 3/4 in. (600 mm)	23 3/4 in. (600 mm)
179	23 7/8 in. (605 mm)	23 7/8 in. (605 mm)
180	24 in. (609.6 mm)	24 in. (609.6 mm)
181	24 1/8 in. (614 mm)	24 1/8 in. (614 mm)
182	24 1/4 in. (617 mm)	24 1/4 in. (617 mm)
183	24 1/2 in. (621 mm)	24 1/2 in. (621 mm)
184	24 3/4 in. (625 mm)	24 3/4 in. (625 mm)
185	24 7/8 in. (630 mm)	24 7/8 in. (630 mm)
186	25 in. (635 mm)	25 in. (635 mm)
187	25 1/8 in. (640 mm)	25 1/8 in. (640 mm)
188	25 1/4 in. (643 mm)	25 1/4 in. (643 mm)
189	25 1/2 in. (646 mm)	25 1/2 in. (646 mm)
190	25 3/4 in. (650 mm)	25 3/4 in. (650 mm)
191	25 7/8 in. (655 mm)	25 7/8 in. (655 mm)
192	26 in. (659.6 mm)	26 in. (659.6 mm)
193	26 1/8 in. (664 mm)	26 1/8 in. (664 mm)
194	26 1/4 in. (667 mm)	26 1/4 in. (667 mm)
195	26 1/2 in. (671 mm)	26 1/2 in. (671 mm)
196	26 3/4 in. (675 mm)	26 3/4 in. (675 mm)
197	26 7/8 in. (680 mm)	26 7/8 in. (680 mm)
198	27 in. (685.8 mm)	27 in. (685.8 mm)
199	27 1/8 in. (690 mm)	27 1/8 in. (690 mm)
200	27 1/4 in. (693 mm)	27 1/4 in. (693 mm)
201	27 1/2 in. (697 mm)	27 1/2 in. (697 mm)
202	27 3/4 in. (701 mm)	27 3/4 in. (701 mm)
203	27 7/8 in. (706 mm)	27 7/8 in. (706 mm)
204	28 in. (711.2 mm)	28 in. (711.2 mm)
205	28 1/8 in. (716 mm)	28 1/8 in. (716 mm)
206	28 1/4 in. (719 mm)	28 1/4 in. (719 mm)
207	28 1/2 in. (723 mm)	28 1/2 in. (723 mm)
208	28 3/4 in. (727 mm)	28 3/4 in. (727 mm)
209	28 7/8 in. (732 mm)	28 7/8 in. (732 mm)
210	29 in. (736.6 mm)	29 in. (736.6 mm)
211	29 1/8 in. (741 mm)	29 1/8 in. (741 mm)
212	29 1/4 in. (744 mm)	29 1/4 in. (744 mm)
213	29 1/2 in. (748 mm)	29 1/2 in. (748 mm)
214	29 3/4 in. (752 mm)	29 3/4 in. (752 mm)
215	29 7/8 in. (757 mm)	29 7/8 in. (757 mm)
216	30 in. (762 mm)	30 in. (762 mm)
217	30 1/8 in. (767 mm)	30 1/8 in. (767 mm)
218	30 1/4 in. (770 mm)	30 1/4 in. (770 mm)
219	30 1/2 in. (774 mm)	30 1/2 in. (774 mm)
220	30 3/4 in. (778 mm)	30 3/4 in. (778 mm)
221	30 7/8 in. (783 mm)	30 7/8 in. (783 mm)
222	31 in. (787.4 mm)	31 in. (787.4 mm)
223	31 1/8 in. (792 mm)	31 1/8 in. (792 mm)
224	31 1/4 in. (795 mm)	31 1/4 in. (795 mm)
225	31 1/2 in. (799 mm)	31 1/2 in. (799 mm)
226	31 3/4 in. (803 mm)	31 3/4 in. (803 mm)
227	31 7/8 in. (808 mm)	31 7/8 in. (808 mm)
228	32 in. (812.8 mm)	32 in. (812.8 mm)
229	32 1/8 in. (817 mm)	32 1/8 in. (817 mm)
230	32 1/4 in. (820 mm)	32 1/4 in. (820 mm)
231	32 1/2 in. (824 mm)	32 1/2 in. (824 mm)
232	32 3/4 in. (828 mm)	32 3/4 in. (828 mm)
233	32 7/8 in. (833 mm)	32 7/8 in. (833 mm)
234	33 in. (838 mm)	33 in. (838 mm)
235	33 1/8 in. (843 mm)	33 1/8 in. (843 mm)
236	33 1/4 in. (846 mm)	33 1/4 in. (846 mm)
237	33 1/2 in. (850 mm)	33 1/2 in. (850 mm)
238	33 3/4 in. (854 mm)	33 3/4 in. (854 mm)
239	33 7/8 in. (859 mm)	33 7/8 in. (859 mm)
240	34 in. (863.2 mm)	34 in. (863.2 mm)
241	34 1/8 in. (868 mm)	34 1/8 in. (868 mm)
242	34 1/4 in. (871 mm)	34 1/4 in. (871 mm)
243	34 1/2 in. (875 mm)	34 1/2 in. (875 mm)
244	34 3/4 in. (879 mm)	34 3/4 in. (879 mm)
245	34 7/8 in. (884 mm)	34 7/8 in. (884 mm)
246	35 in. (889 mm)	35 in. (889 mm)
247	35 1/8 in. (894 mm)	35 1/8 in. (894 mm)
248	35 1/4 in. (897 mm)	35 1/4 in. (897 mm)
249	35 1/2 in. (901 mm)	35 1/2 in. (901 mm)
250	35 3/4 in. (905 mm)	35 3/4 in. (905 mm)
251	35 7/8 in. (910 mm)	35 7/8 in. (910 mm)
252	36 in. (914.4 mm)	36 in. (914.4 mm)
253	36 1/8 in. (919 mm)	36 1/8 in. (919 mm)
254	36 1/4 in. (922 mm)	36 1/4 in. (922 mm)
255	36 1/2 in. (926 mm)	36 1/2 in. (926 mm)
256	36 3/4 in. (930 mm)	36 3/4 in. (930 mm)
257	36 7/8 in. (935 mm)	36 7/8 in. (935 mm)
258	37 in. (939.8 mm)	37 in. (939.8 mm)
259	37 1/8 in. (944 mm)	37 1/8 in. (944 mm)
260	37 1/4 in. (947 mm)	37 1/4 in. (947 mm)
261	37 1/2 in. (951 mm)	37 1/2 in. (951 mm)
262	37 3/4 in. (955 mm)	37 3/4 in. (955 mm)
263	37 7/8 in. (960 mm)	37 7/8 in. (960 mm)
264	38 in. (964.8 mm)	38 in. (964.8 mm)
265	38 1/8 in. (969 mm)	38 1/8 in. (969 mm)
266	38 1/4 in. (972 mm)	38 1/4 in. (972 mm)
267	38 1/2 in. (976 mm)	38 1/2 in. (976 mm)
268	38 3/4 in. (980 mm)	38 3/4 in. (980 mm)
269	38 7/8 in. (985 mm)	38 7/8 in. (985 mm)
270	39 in. (989.2 mm)	39 in. (989.2 mm)
271	39 1/8 in. (994 mm)	39 1/8 in. (994 mm)
272	39 1/4 in. (997 mm)	39 1/4 in. (997 mm)
273	39 1/2 in. (1001 mm)	39 1/2 in. (1001 mm)
274	39 3/4 in. (1005 mm)	39 3/4 in. (1005 mm)
275	39 7/8 in. (1010 mm)	39 7/8 in. (1010 mm)
276	40 in. (1016 mm)	40 in. (1016 mm)
277	40 1/8 in. (1021 mm)	40 1/8 in. (1021 mm)
278	40 1/4 in. (1024 mm)	40 1/4 in. (1024 mm)
279	40 1/2 in. (1028 mm)	40 1/2 in. (1028 mm)
280	40 3/4 in. (1032 mm)	40 3/4 in. (1032 mm)
281	40 7/8 in. (1037 mm)	40 7/8 in. (1037 mm)
282	41 in. (1041.4 mm)	41 in. (1041.4 mm)
283	41 1/8 in. (1046 mm)	41 1/8 in. (1046 mm)
284	41 1/4 in. (1049 mm)	41 1/4 in. (1049 mm)
285	41 1/2 in. (1053 mm)	41 1/2 in. (1053 mm)
286	41 3/4 in. (1057 mm)	41 3/4 in. (1057 mm)
287	41 7/8 in. (1062 mm)	41 7/8 in. (1062 mm)
288	42 in. (1066.8 mm)	42 in. (1066.8 mm)
289	42 1/8 in. (1071 mm)	42 1/8 in. (1071 mm)
290	42 1/4 in. (1074 mm)	42 1/4 in. (1074 mm)
291	42 1/2 in. (1078 mm)	42 1/2 in. (1078 mm)
292	42 3/4 in. (1082 mm)	42 3/4 in. (1082 mm)
293	42 7/8 in. (1087 mm)	42 7/8 in. (1087 mm)
294	43 in. (1091.6 mm)	43 in. (1091.6 mm)
295	43 1/8 in. (1096 mm)	43 1/8 in. (1096 mm)
296	43 1/4 in. (1099 mm)	43 1/4 in. (1099 mm)
297	43 1/2 in. (1103 mm)	43 1/2 in. (1103 mm)
298	43 3/4 in. (1107 mm)	43 3/4 in. (1107 mm)
299	43 7/8 in. (1112 mm)	43 7/8 in. (1112 mm)
300	44 in. (1117.6 mm)	44 in. (1117.6 mm)
301	44 1/8 in. (1122 mm)	44 1/8 in. (1122 mm)
302	44 1/4 in. (1125 mm)	44 1/4 in. (1125 mm)
303	44 1/2 in. (1129 mm)	44 1/2 in. (1129 mm)
304	44 3/4 in. (1133 mm)	44 3/4 in. (1133 mm)
305	44 7/8 in. (1138 mm)	44 7/8 in. (1138 mm)
306	45 in. (1143 mm)	45 in. (1143 mm)
307	45 1/8 in. (1148 mm)	45 1/8 in. (1148 mm)
308	45 1/4 in. (1151 mm)	45 1/4 in. (1151 mm)
309	45 1/2 in. (1155 mm)	45 1/2 in. (1155 mm)
310	45 3/4 in. (1159 mm)	45 3/4 in. (1159 mm)
311	45 7/8 in. (1164 mm)	45 7/8 in. (1164 mm)
312	46 in. (1168.3 mm)	46 in. (1168.3 mm)
313	46 1/8 in. (1173 mm)	46 1/8 in. (1173 mm)
314	46 1/4 in. (1176 mm)	46 1/4 in. (1176 mm)
315	46 1/2 in. (1180 mm)	46