| Equipment ID VIN Year OTRT H09263 5V8VC5320ST501699 2025 XTRA Lease DOT / BIT Inspection Check Mark = OK X = Needs Further Attention Repaired Glad Hands & Rubber Grommets Check Mark = OK X = Needs Further Attention Repaired 7-Way Electrical Plug Repaired Su Program Registration, Valid License Plate and sticker Repaired Su Lights, Wiring and Splice Conditions Repaired Program Exterior Trailer - Body Condition and Coupling Device Repaired Program Corner Locking Devices Repaired Tire | VIN Year 5V8VC5320ST501699 2025 XTRA Lease DOT / BIT Inspecti Check Mark = OK X = Needs Further Attentio & Rubber Grommets Repaired rical Plug Repaired Valid License Plate and sticker Repaired g and Splice Conditions Repaired ler - Body Condition and Coupling Device Repaired ing Devices Repaired | VIN Year 5V8VC5320ST501699 2025 XTRA Lease DOT / BIT Inspecti Check Mark = OK X = Needs Further Attentio & Rubber Grommets Repaired rical Plug Repaired Valid License Plate and sticker Repaired g and Splice Conditions Repaired ler - Body Condition and Coupling Device Repaired ing Devices Repaired | VIN Year 5V8VC5320ST501699 2025 XTRA Lease DOT / BIT Inspecti Check Mark = OK X = Needs Further Attentio & Rubber Grommets Repaired rical Plug Repaired Valid License Plate and sticker Repaired g and Splice Conditions Repaired ler - Body Condition and Coupling Device Repaired ing Devices Repaired |
|---|---|---|--|
| Solidage Year XTRA Lease DOT / BIT Inspecti X = Needs Further Attention Repaired Repaired </td <td>Vear 2025 XTRA Lease DOT / BIT Inspecti Check Mark = OK X = Needs Further Attentio Repaired Repaired Repaired Repaired Repaired Repaired Icker Repaired ng - Lubricate & Cycle Repaired rion and check for Leaks Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired ng - Lubricate & Cycle Repaired Repaired Repaired</td> <td>Vear 2025 XTRA Lease DOT / BIT Inspecti Check Mark = OK X = Needs Further Attentio Repaired Repaired Repaired Repaired Repaired Repaired Icker Repaired ng - Lubricate & Cycle Repaired rion and check for Leaks Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired ng - Lubricate & Cycle Repaired Repaired Repaired</td> <td>Vear Manufacturer (ANGUARD XTRA Lease DOT / BIT Inspection and PM Worksheet Check Mark = OK X = Needs Further Attention R = Repaired NA = Not Applicable Repaired Repaired Stub-Frame – Silde Rais and Crossmembers Repaired Repaired Acrodynamic Side Skirts Icker Repaired Stider Mechanism & Locking Pins - Lubricate, Release engage Proper Lubricant Level in each Wheel End - Fill if neo- engage Inp Lubricate & Cycle Repaired Wheels - Check for Cracks / Tire Matching Repaired Wheels - Check for Cracks / Tire Matching Infing Repaired Winfing Repaired Wheels - Check for Cracks / Tire Matching Proper Lubricate & Cycle Repaired Repaired Mudflas, Brackets, and Rubber Dock Bumpers Repaired Mudflas, Brackets, and Rubber Dock Bumpers Repaired Worksheet Lubricate Repaired Worksheet Stocks - Lubricate Repaired W</td> | Vear 2025 XTRA Lease DOT / BIT Inspecti Check Mark = OK X = Needs Further Attentio Repaired Repaired Repaired Repaired Repaired Repaired Icker Repaired ng - Lubricate & Cycle Repaired rion and check for Leaks Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired ng - Lubricate & Cycle Repaired Repaired Repaired | Vear 2025 XTRA Lease DOT / BIT Inspecti Check Mark = OK X = Needs Further Attentio Repaired Repaired Repaired Repaired Repaired Repaired Icker Repaired ng - Lubricate & Cycle Repaired rion and check for Leaks Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired repaired Repaired ng - Lubricate & Cycle Repaired Repaired Repaired | Vear Manufacturer (ANGUARD XTRA Lease DOT / BIT Inspection and PM Worksheet Check Mark = OK X = Needs Further Attention R = Repaired NA = Not Applicable Repaired Repaired Stub-Frame – Silde Rais and Crossmembers Repaired Repaired Acrodynamic Side Skirts Icker Repaired Stider Mechanism & Locking Pins - Lubricate, Release engage Proper Lubricant Level in each Wheel End - Fill if neo- engage Inp Lubricate & Cycle Repaired Wheels - Check for Cracks / Tire Matching Repaired Wheels - Check for Cracks / Tire Matching Infing Repaired Winfing Repaired Wheels - Check for Cracks / Tire Matching Proper Lubricate & Cycle Repaired Repaired Mudflas, Brackets, and Rubber Dock Bumpers Repaired Mudflas, Brackets, and Rubber Dock Bumpers Repaired Worksheet Lubricate Repaired Worksheet Stocks - Lubricate Repaired W |
| OT / BIT Inspecti Repaired R | OT / BIT Inspecti Repaired R | OT / BIT Inspecti Repaired R | r Manufacturer VANGUARD OT / BIT Inspection and PM Worksheet Repaired Repaired NA = Not Applicable Repaired Repaired Repaired Sub-Frame – Side Rails and Crossmembers Repaired Repaired Slider Mechanism & Locking Pins - Lubricate, Release engage Repaired Slider Mechanism & Locking Pins - Lubricate, Release Repaired Repaired Slider Mechanism & Locking Pins - Lubricate, Release engage Repaired Slider Mechanism & Locking Pins - Lubricate, Release engage Repaired Slider Mechanism & Locking Pins - Lubricate, Release engage Repaired Slider Mechanism & Locking Pins - Lubricate, Release engage Repaired Wheels - Check for Cracks / Tire Matching Repaired Mudflaps, Frackets, and Rubber Dock Bumpers Repaired Mudflaps, Brackets, and Rubber Dock Bumpers Repaired Repaired Door Hold Backs and Pull Handles - Present & Funct Repaired Repaired Nucflaps, Rollers, Locks - Lubricate Repaired Repaired Note: Trailer - Floor, Roof, and Side Walls Repaired Repaired Not Tiler Repaired Note: Taler - Floor, Roof, and Side Walls Repaired Repaired Note: Taler - Floor, Roof, and Side Walls Repaired Repaired Note: Taler - Sticker Applied Repaired Rep |
| BIT Inspection Further Attention paired pai | Manufacturer VANGUARD BIT Inspection and PM Work Further Attention R = Repaired paired Sub-Frame - Slide Rapage paired Slider Mechanism & Logengage paired Slider Mechanism & Logengage paired Slider Mechanism & Logengage paired Proper Lubricant Level engage paired Wheels - Check for Crame - Slide Rapaired paired Wheels - Check for Crame - Slide Rapaired paired Wheels - Check for Crame - Slide Rapaired paired Conspicuity Tape-Side paired All Hinges, Brackets, ar paired All Hinges, Rollers, Logend paired Door Hold Backs and P paired NOTES: aired NoTES: aired <td>Manufacturer VANGUARD BIT Inspection and PM Worksheet Further Attention R = Repaired N/A = Not Applicable paired Aerodynamic Side Rails and Crossmember engage Proper Lubricant Level in each Wheel End - In Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Doors - Free of Impermissible damage or weat Lugnuts - Torque to 450-500 ft/lbs - Set wre Conspicuity Tape-Side Panels, Rear Doors, Mudflaps, Brackets, and Rubber Dock Bump Mudflaps, Rollers, Locks - Lubricate Interior Trailer - Floor, Roof, and Side Walls aired Door Hold Backs and Pull Handles - Present Multifumith (<i>QD</i>) All Hinges, Rollers, Locks - Lubricate aired Door Trailer - Floor, Roof, and Side Walls aired NoTES: Brakes (Drum in 8ths / ADB in mm And Arther Con All Arte Position Depth All Kindel Position Depth All Kindel Position Depth All Kindel All Kindel Arear All Kindel Arear Arear All Kindel Arear All Kindel Arear All Kindel Arear</td> <td>Manufacturer VANGUARD On and PM Worksheet R = Repaired N/A = Not Applicable N/A = Not Applicable Sub-Frame - Slide Rails and Crossmembers erodynamic Side Skirts Slider Mechanism & Locking Pins - Lubricate, Release proper Lubricant Level in each Wheel End - Fill if nec Yheels - Check for Cracks / Tire Matching rires - free of impermissible damage or wear ugnuts - Torque to 450-500 ft/lbs - Set wrench to 5 fetal Flow-Thru Valve Stem Caps Oors - Proper Operation oor Hold Backs and Pull Handles - Present & Funct II Hinges, Rollers, Locks - Lubricate alifornia BIT Inspected & Passed Sterior - Resecure Plywood as Needed Axle Position Axle Position Hubo: 1 <u>Rear</u> The Front 2 <u>L Middle</u> Prot. Ti 2 <u>L Middle</u> Prot. Ti</td> | Manufacturer VANGUARD BIT Inspection and PM Worksheet Further Attention R = Repaired N/A = Not Applicable paired Aerodynamic Side Rails and Crossmember engage Proper Lubricant Level in each Wheel End - In Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Proper Lubricant Level in each Wheel End - In Paired Doors - Free of Impermissible damage or weat Lugnuts - Torque to 450-500 ft/lbs - Set wre Conspicuity Tape-Side Panels, Rear Doors, Mudflaps, Brackets, and Rubber Dock Bump Mudflaps, Rollers, Locks - Lubricate Interior Trailer - Floor, Roof, and Side Walls aired Door Hold Backs and Pull Handles - Present Multifumith (<i>QD</i>) All Hinges, Rollers, Locks - Lubricate aired Door Trailer - Floor, Roof, and Side Walls aired NoTES: Brakes (Drum in 8ths / ADB in mm And Arther Con All Arte Position Depth All Kindel Position Depth All Kindel Position Depth All Kindel All Kindel Arear All Kindel Arear Arear All Kindel Arear All Kindel Arear All Kindel Arear | Manufacturer VANGUARD On and PM Worksheet R = Repaired N/A = Not Applicable N/A = Not Applicable Sub-Frame - Slide Rails and Crossmembers erodynamic Side Skirts Slider Mechanism & Locking Pins - Lubricate, Release proper Lubricant Level in each Wheel End - Fill if nec Yheels - Check for Cracks / Tire Matching rires - free of impermissible damage or wear ugnuts - Torque to 450-500 ft/lbs - Set wrench to 5 fetal Flow-Thru Valve Stem Caps Oors - Proper Operation oor Hold Backs and Pull Handles - Present & Funct II Hinges, Rollers, Locks - Lubricate alifornia BIT Inspected & Passed Sterior - Resecure Plywood as Needed Axle Position Axle Position Hubo: 1 <u>Rear</u> The Front 2 <u>L Middle</u> Prot. Ti 2 <u>L Middle</u> Prot. Ti |
| | Manufacturer VANGUARD and PM Work R = Repaired N o-Frame – Slide Ra odynamic Side Skir lage eels - Check for Cra eels - Check for Cra eels - Check for Cra ss - free of impermis per Lubricant Level eels - Check for Cra eels - Check for Cra ss - free of impermis nuts – Torque to 4: illaps, Brackets, ar ar Impact Guard finges, Rollers Cherat or Hold Backs and F finspected – Stick fornia BIT Inspecte Axle Posit Axle Posit 2 L Midd 3 R Rear | Manufacturer VANGUARD and PM Worksheet R = Repaired N/A = Not Applicable o-Frame – Slide Rails and Crossmember odynamic Side Skirts ier Mechanism & Locking Pins - Lubricate age ser free of impermissible damage or wear inuts – Torque to 450-500 ft/lbs – Set wrg ial Flow-Thru Valve Stem Caps sspicuity Tape–Side Panels, Rear Doors, afflaps, Brackets, and Rubber Dock Bump or Hold Backs and Pull Handles - Present linges, Rollers, Locks – Lubricate rior Trailer – Floor, Roof, and Side Walls rornia BIT Inspected & Passed fornia BIT Inspected & Passed Brakes (Drum in 8ths / ADB in mm) Axle Position Axle Position | Manufacturer VANGUARD and PM Worksheet R = Repaired N/A = Not Applicable o-Frame – Slide Rails and Crossmembers odynamic Side Skirts ler Mechanism & Locking Pins - Lubricate, Release lage sels - Check for Cracks / Tire Matching ss - free of impermissible damage or wear nuts – Torque to 450-500 ft/bs – Set wrench to 5 al Flow-Thru Valve Stem Caps spicuity Tape–Side Panels, Rear Doors, Headbo finaps, Brackets, and Rubber Dock Bumpers r Impact Guard rs – Proper Operation r Hold Backs and Pull Handles - Present & Funct finspected – Sticker Applied fornia BIT Inspected & Passed Sticker Applied fornia BIT Inspected & Passed Axie Position Axie Position Axie Front Axie Front Axie Front Rear Yend Kear Yend Rear Rear Struct Plymoid as Needed Fuel the Prot. Tri Rear |

inspection conducted by:_ (Inspector signature) Inspection Date: 11-11 いたい

Company Name: Cox Automotive Mobility Fleet Services

Print Name:

MACUN NONATI