

ANNUAL VEHICLE INSPECTION REPORT

VEHICLE HISTORY RECORD

REPORT NUMBER	FLEET UNIT NUMBER	DATE
610483934	761	07/23/24

MOTOR CARRIER OPERATOR

Zig. Freight Inc dba Royal 3 Inc

ADDRESS
6850 W. 63rd St.

CITY, STATE, ZIP CODE

Chicago, IL 60638

VEHICLE TYPE ☐ TRACTOR ☐ TRAILER ☒ TRUCK ☐ BUS
☐ (OTHER)

INSPECTOR'S NAME (PRINT OR TYPE)

Jugoslav Kovacevic

THIS INSPECTOR MEETS THE QUALIFICATION REQUIREMENTS IN SECTION 396.19.

☒ YES

VEHICLE IDENTIFICATION (✓ AND COMPLETE)

☐ LIC. PLATE NO. ☒ VIN ☐ OTHER 3AKJH4D20PSUA1585

INSPECTION AGENCY/LOCATION (OPTIONAL)

VEHICLE COMPONENTS INSPECTED

OK	NEEDS REPAIR	REPAIRED DATE	ITEM	OK	NEEDS REPAIR	REPAIRED DATE	ITEM
✓			1. BRAKE SYSTEM	✓			e. Pitman Arm
✓			a. Service Brakes	✓			f. Power Steering
✓			b. Parking Brake System	✓			g. Ball and Socket Joints
✓			c. Brake Drums or Rotors	✓			h. Tie Rods and Drag Links
✓			d. Brake Hose	✓			i. Nuts
✓			e. Brake Tubing	✓			j. Steering System
✓			f. Low Pressure Warning Device	✓			8. SUSPENSION
✓			g. Tractor Protection Valve	✓			a. Axle Positioning Parts
✓			h. Air Compressor	✓			b. Spring Assembly
✓			i. Electric Brakes	✓			c. Torque, Radius or Tracking Components
✓			j. Hydraulic Brakes	✓			9. FRAME
✓			k. Vacuum Systems	✓			a. Frame Members
✓			l. Antilock Brake System	✓			b. Tire and Wheel Clearance
✓			m. Automatic Brake Adjusters	✓			c. Adjustable Axle Assemblies (Sliding Subframes)
✓			2. COUPLING DEVICES	✓			10. TIRES
✓			a. Fifth Wheels	✓			a. Steer-Axle Tires
✓			b. Pintle Hooks	✓			b. All Other Tires
✓			c. Drawbar/Towbar Eye	✓			c. Speed-Restricted Tires
✓			d. Drawbar/Towbar Tongue	✓			11. WHEELS AND RIMS
✓			e. Safety Devices	✓			a. Lock or Side Ring
✓			f. Saddle-Mounts	✓			b. Wheels and Rims
✓			3. EXHAUST SYSTEM	✓			c. Fasteners
✓			a. No leaks forward of/directly below the driver/sleeper compartment.	✓			d. Welds
✓			b. Bus: No leaking/discharging in violation of standard.	✓			12. WINDSHIELD GLAZING
✓			c. Unlikely to burn, char, or damage the electrical wiring, fuel supply, or any combustible part of vehicle.	✓			No cracks, discoloration, obstacles, etc. (see 393.60 for exceptions).
✓			4. FUEL SYSTEM	✓			13. WINDSHIELD WIPERS
✓			a. No visible leak.	✓			Any power unit that has an inoperative wiper, or missing or damaged parts that render it ineffective.
✓			b. Fuel Tank Filler Cap	✓			14. MOTORCOACH SEATS
✓			c. Fuel tank securely attached.	✓			Any passenger seat that is not securely fastened to the vehicle structure.
✓			5. LIGHTING DEVICES	✓			15. REAR IMPACT GUARD
✓			All lighting devices and reflectors required by Section 393 shall be operable.	✓			In place, securely attached, proper size, proper placement (see 393.86).
✓			6. SAFE LOADING	✓			16. OTHER
✓			a. Vehicle parts, load, dunnage, spare tire, etc., secured.	✓			List any other condition(s) which may prevent safe operation of this vehicle.
✓			b. Front End Structure	✓			
✓			c. Intermodal Container Securement Devices	✓			
✓			7. STEERING MECHANISM	✓			
✓			a. Steering Wheel Free Play	✓			
✓			b. Steering Column	✓			
✓			c. Front Axle Beam/All Other Steering Components	✓			
✓			d. Steering Gear Box	✓			

INSTRUCTIONS: MARK COLUMN ENTRIES TO VERIFY INSPECTION: ☒ OK, ☒ NEEDS REPAIR, ☒ IF ITEMS DO NOT APPLY, _____ REPAIRED DATE

CERTIFICATION: THIS VEHICLE HAS PASSED ALL THE INSPECTION ITEMS FOR THE ANNUAL VEHICLE INSPECTION IN ACCORDANCE WITH 49 CFR PART 396.

Part 396, Appendix A – Minimum Periodic Inspection Standards

A vehicle does not pass an inspection if it has one of the following defects or deficiencies:

1. **Brake System**

(1) Absence of braking action on any axle required to have brakes (such as upon application of the service brakes (such as disc brakes), or 2 the governor cut-out pressure, or does not operate at 55 psi and below, or 1/2 the governor cut-out pressure, whichever is less.

(2) Missing or broken mechanical components including: struts, lining, pads, springs, anchor pin, spiders, cam rollers, push-rod, and air chamber mounting bolts.

(3) Loose brake components including air chambers, spiders, and cam shaft support bolts.

(4) Audible air leak at brake chamber (Example: unclipped diaphragm, loose chamber).

(5) Readjustment limits. The maximum pushed stroke must not be greater than the values given in the tables below and at §393.47(e). Any brake stroke exceeding the readjustment limit will be rejected. Stroke must be measured with 90 psi of air and reservoir pressure of 80 to 90 psi with brakes fully applied.

CLAMP-Type Brake Chambers

Type	Outside diameter	Brake readjustment limit
30	8 1/8 in. (208 mm)	2 1/8 in. (57.2 mm)
36	9 1/8 in. (235 mm)	2 1/8 in. (57.2 mm)
42	10 1/8 in. (264 mm)	2 1/8 in. (57.2 mm)
48	11 1/8 in. (289 mm)	2 1/8 in. (57.2 mm)
54	12 1/8 in. (312 mm)	2 1/8 in. (57.2 mm)
60	13 1/8 in. (338 mm)	2 1/8 in. (57.2 mm)
66	14 1/8 in. (363 mm)	2 1/8 in. (57.2 mm)
72	15 1/8 in. (390 mm)	2 1/8 in. (57.2 mm)
78	16 1/8 in. (415 mm)	2 1/8 in. (57.2 mm)
84	17 1/8 in. (440 mm)	2 1/8 in. (57.2 mm)
90	18 1/8 in. (465 mm)	2 1/8 in. (57.2 mm)
96	19 1/8 in. (490 mm)	2 1/8 in. (57.2 mm)
102	20 1/8 in. (515 mm)	2 1/8 in. (57.2 mm)
108	21 1/8 in. (540 mm)	2 1/8 in. (57.2 mm)
114	22 1/8 in. (565 mm)	2 1/8 in. (57.2 mm)
120	23 1/8 in. (590 mm)	2 1/8 in. (57.2 mm)
126	24 1/8 in. (615 mm)	2 1/8 in. (57.2 mm)
132	25 1/8 in. (640 mm)	2 1/8 in. (57.2 mm)
138	26 1/8 in. (665 mm)	2 1/8 in. (57.2 mm)
144	27 1/8 in. (690 mm)	2 1/8 in. (57.2 mm)
150	28 1/8 in. (715 mm)	2 1/8 in. (57.2 mm)
156	29 1/8 in. (740 mm)	2 1/8 in. (57.2 mm)
162	30 1/8 in. (765 mm)	2 1/8 in. (57.2 mm)
168	31 1/8 in. (790 mm)	2 1/8 in. (57.2 mm)
174	32 1/8 in. (815 mm)	2 1/8 in. (57.2 mm)
180	33 1/8 in. (840 mm)	2 1/8 in. (57.2 mm)
186	34 1/8 in. (865 mm)	2 1/8 in. (57.2 mm)
192	35 1/8 in. (890 mm)	2 1/8 in. (57.2 mm)
198	36 1/8 in. (915 mm)	2 1/8 in. (57.2 mm)
204	37 1/8 in. (940 mm)	2 1/8 in. (57.2 mm)
210	38 1/8 in. (965 mm)	2 1/8 in. (57.2 mm)
216	39 1/8 in. (990 mm)	2 1/8 in. (57.2 mm)
222	40 1/8 in. (1015 mm)	2 1/8 in. (57.2 mm)
228	41 1/8 in. (1040 mm)	2 1/8 in. (57.2 mm)
234	42 1/8 in. (1065 mm)	2 1/8 in. (57.2 mm)
240	43 1/8 in. (1090 mm)	2 1/8 in. (57.2 mm)
246	44 1/8 in. (1115 mm)	2 1/8 in. (57.2 mm)
252	45 1/8 in. (1140 mm)	2 1/8 in. (57.2 mm)
258	46 1/8 in. (1165 mm)	2 1/8 in. (57.2 mm)
264	47 1/8 in. (1190 mm)	2 1/8 in. (57.2 mm)
270	48 1/8 in. (1215 mm)	2 1/8 in. (57.2 mm)
276	49 1/8 in. (1240 mm)	2 1/8 in. (57.2 mm)
282	50 1/8 in. (1265 mm)	2 1/8 in. (57.2 mm)
288	51 1/8 in. (1290 mm)	2 1/8 in. (57.2 mm)
294	52 1/8 in. (1315 mm)	2 1/8 in. (57.2 mm)
300	53 1/8 in. (1340 mm)	2 1/8 in. (57.2 mm)
306	54 1/8 in. (1365 mm)	2 1/8 in. (57.2 mm)
312	55 1/8 in. (1390 mm)	2 1/8 in. (57.2 mm)
318	56 1/8 in. (1415 mm)	2 1/8 in. (57.2 mm)
324	57 1/8 in. (1440 mm)	2 1/8 in. (57.2 mm)
330	58 1/8 in. (1465 mm)	2 1/8 in. (57.2 mm)
336	59 1/8 in. (1490 mm)	2 1/8 in. (57.2 mm)
342	60 1/8 in. (1515 mm)	2 1/8 in. (57.2 mm)
348	61 1/8 in. (1540 mm)	2 1/8 in. (57.2 mm)
354	62 1/8 in. (1565 mm)	2 1/8 in. (57.2 mm)
360	63 1/8 in. (1590 mm)	2 1/8 in. (57.2 mm)
366	64 1/8 in. (1615 mm)	2 1/8 in. (57.2 mm)
372	65 1/8 in. (1640 mm)	2 1/8 in. (57.2 mm)
378	66 1/8 in. (1665 mm)	2 1/8 in. (57.2 mm)
384	67 1/8 in. (1690 mm)	2 1/8 in. (57.2 mm)
390	68 1/8 in. (1715 mm)	2 1/8 in. (57.2 mm)
396	69 1/8 in. (1740 mm)	2 1/8 in. (57.2 mm)
402	70 1/8 in. (1765 mm)	2 1/8 in. (57.2 mm)
408	71 1/8 in. (1790 mm)	2 1/8 in. (57.2 mm)
414	72 1/8 in. (1815 mm)	2 1/8 in. (57.2 mm)
420	73 1/8 in. (1840 mm)	2 1/8 in. (57.2 mm)
426	74 1/8 in. (1865 mm)	2 1/8 in. (57.2 mm)
432	75 1/8 in. (1890 mm)	2 1/8 in. (57.2 mm)
438	76 1/8 in. (1915 mm)	2 1/8 in. (57.2 mm)
444	77 1/8 in. (1940 mm)	2 1/8 in. (57.2 mm)
450	78 1/8 in. (1965 mm)	2 1/8 in. (57.2 mm)
456	79 1/8 in. (1990 mm)	2 1/8 in. (57.2 mm)
462	80 1/8 in. (2015 mm)	2 1/8 in. (57.2 mm)
468	81 1/8 in. (2040 mm)	2 1/8 in. (57.2 mm)
474	82 1/8 in. (2065 mm)	2 1/8 in. (57.2 mm)
480	83 1/8 in. (2090 mm)	2 1/8 in. (57.2 mm)
486	84 1/8 in. (2115 mm)	2 1/8 in. (57.2 mm)
492	85 1/8 in. (2140 mm)	2 1/8 in. (57.2 mm)
498	86 1/8 in. (2165 mm)	2 1/8 in. (57.2 mm)
504	87 1/8 in. (2190 mm)	2 1/8 in. (57.2 mm)
510	88 1/8 in. (2215 mm)	2 1/8 in. (57.2 mm)
516	89 1/8 in. (2240 mm)	2 1/8 in. (57.2 mm)
522	90 1/8 in. (2265 mm)	2 1/8 in. (57.2 mm)
528	91 1/8 in. (2290 mm)	2 1/8 in. (57.2 mm)
534	92 1/8 in. (2315 mm)	2 1/8 in. (57.2 mm)
540	93 1/8 in. (2340 mm)	2 1/8 in. (57.2 mm)
546	94 1/8 in. (2365 mm)	2 1/8 in. (57.2 mm)
552	95 1/8 in. (2390 mm)	2 1/8 in. (57.2 mm)
558	96 1/8 in. (2415 mm)	2 1/8 in. (57.2 mm)
564	97 1/8 in. (2440 mm)	2 1/8 in. (57.2 mm)
570	98 1/8 in. (2465 mm)	2 1/8 in. (57.2 mm)
576	99 1/8 in. (2490 mm)	2 1/8 in. (57.2 mm)
582	100 1/8 in. (2515 mm)	2 1/8 in. (57.2 mm)
588	101 1/8 in. (2540 mm)	2 1/8 in. (57.2 mm)
594	102 1/8 in. (2565 mm)	2 1/8 in. (57.2 mm)
600	103 1/8 in. (2590 mm)	2 1/8 in. (57.2 mm)
606	104 1/8 in. (2615 mm)	2 1/8 in. (57.2 mm)
612	105 1/8 in. (2640 mm)	2 1/8 in. (57.2 mm)
618	106 1/8 in. (2665 mm)	2 1/8 in. (57.2 mm)
624	107 1/8 in. (2690 mm)	2 1/8 in. (57.2 mm)
630	108 1/8 in. (2715 mm)	2 1/8 in. (57.2 mm)
636	109 1/8 in. (2740 mm)	2 1/8 in. (57.2 mm)
642	110 1/8 in. (2765 mm)	2 1/8 in. (57.2 mm)
648	111 1/8 in. (2790 mm)	2 1/8 in. (57.2 mm)
654	112 1/8 in. (2815 mm)	2 1/8 in. (57.2 mm)
660	113 1/8 in. (2840 mm)	2 1/8 in. (57.2 mm)
666	114 1/8 in. (2865 mm)	2 1/8 in. (57.2 mm)
672	115 1/8 in. (2890 mm)	2 1/8 in. (57.2 mm)
678	116 1/8 in. (2915 mm)	2 1/8 in. (57.2 mm)
684	117 1/8 in. (2940 mm)	2 1/8 in. (57.2 mm)
690	118 1/8 in. (2965 mm)	2 1/8 in. (57.2 mm)
696	119 1/8 in. (2990 mm)	2 1/8 in. (57.2 mm)
702	120 1/8 in. (3015 mm)	2 1/8 in. (57.2 mm)
708	121 1/8 in. (3040 mm)	2 1/8 in. (57.2 mm)
714	122 1/8 in. (3065 mm)	2 1/8 in. (57.2 mm)
720	123 1/8 in. (3090 mm)	2 1/8 in. (57.2 mm)
726	124 1/8 in. (3115 mm)	2 1/8 in. (57.2 mm)
732	125 1/8 in. (3140 mm)	2 1/8 in. (57.2 mm)
738	126 1/8 in. (3165 mm)	2 1/8 in. (57.2 mm)
744	127 1/8 in. (3190 mm)	2 1/8 in. (57.2 mm)
750	128 1/8 in. (3215 mm)	2 1/8 in. (57.2 mm)
756	129 1/8 in. (3240 mm)	2 1/8 in. (57.2 mm)
762	130 1/8 in. (3265 mm)	2 1/8 in. (57.2 mm)
768	131 1/8 in. (3290 mm)	2 1/8 in. (57.2 mm)
774	132 1/8 in. (3315 mm)	2 1/8 in. (57.2 mm)
780	133 1/8 in. (3340 mm)	2 1/8 in. (57.2 mm)
786	134 1/8 in. (3365 mm)	2 1/8 in. (57.2 mm)
792	135 1/8 in. (3390 mm)	2 1/8 in. (57.2 mm)
798	136 1/8 in. (3415 mm)	2 1/8 in. (57.2 mm)
804	137 1/8 in. (3440 mm)	2 1/8 in. (57.2 mm)
810	138 1/8 in. (3465 mm)	2 1/8 in. (57.2 mm)
816	139 1/8 in. (3490 mm)	2 1/8 in. (57.2 mm)
822	140 1/8 in. (3515 mm)	2 1/8 in. (57.2 mm)
828	141 1/8 in. (3540 mm)	2 1/8 in. (57.2 mm)
834	142 1/8 in. (3565 mm)	2 1/8 in. (57.2 mm)
840	143 1/8 in. (3590 mm)	2 1/8 in. (57.2 mm)
846	144 1/8 in. (3615 mm)	2 1/8 in. (57.2 mm)
852	145 1/8 in. (3640 mm)	2 1/8 in. (57.2 mm)
858	146 1/8 in. (3665 mm)	2 1/8 in. (57.2 mm)
864	147 1/8 in. (3690 mm)	2 1/8 in. (57.2 mm)
870	148 1/8 in. (3715 mm)	2 1/8 in. (57.2 mm)
876	149 1/8 in. (3740 mm)	2 1/8 in. (57.2 mm)
882	150 1/8 in. (3765 mm)	2 1/8 in. (57.2 mm)
888	151 1/8 in. (3790 mm)	2 1/8 in. (57.2 mm)
894	152 1/8 in. (3815 mm)	2 1/8 in. (57.2 mm)
900	153 1/8 in. (3840 mm)	2 1/8 in. (57.2 mm)
906	154 1/8 in. (3865 mm)	2 1/8 in. (57.2 mm)
912	155 1/8 in. (3890 mm)	2 1/8 in. (57.2 mm)
918	156 1/8 in. (3915 mm)	2 1/8 in. (57.2 mm)
924	157 1/8 in. (3940 mm)	2 1/8 in. (57.2 mm)
930	158 1/8 in. (3965 mm)	2 1/8 in. (57.2 mm)
936	159 1/8 in. (3990 mm)	2 1/8 in. (57.2 mm)
942	160 1/8 in. (4015 mm)	2 1/8 in. (57.2 mm)
948	161 1/8 in. (4040 mm)	2 1/8 in. (57.2 mm)
954	162 1/8 in. (4065 mm)	2 1/8 in. (57.2 mm)
960	163 1/8 in. (4090 mm)	2 1/8 in. (57.2 mm)
966	164 1/8 in. (4115 mm)	2 1/8 in. (57.2 mm)
972	165 1/8 in. (4140 mm)	2 1/8 in. (57.2 mm)
978	166 1/8 in. (4165 mm)	2 1/8 in. (57.2 mm)
984	167 1/8 in. (4190 mm)	2 1/8 in. (57.2 mm)
990	168 1/8 in. (4215 mm)	2 1/8 in. (57.2 mm)
996	169 1/8 in. (4240 mm)	2 1/8 in. (57.2 mm)
1002	170 1/8 in. (4265 mm)	2 1/8 in. (57.2 mm)
1008	171 1/8 in. (4290 mm)	2 1/8 in. (57.2 mm)
1014	172 1/8 in. (4315 mm)	2 1/8 in. (57.2 mm)
1020	173 1/8 in. (4340 mm)	2 1/8 in. (57.2 mm)
1026	174 1/8 in. (4365 mm)	2 1/8 in. (57.2 mm)
1032	175 1/8 in. (4390 mm)	2 1/8 in. (57.2 mm)
1038	176 1/8 in. (4415 mm)	2 1/8 in. (57.2 mm)
1044	177 1/8 in. (4440 mm)	2 1/8 in. (57.2 mm)
1050	178 1/8 in. (4465 mm)	2 1/8 in. (57.2 mm)
1056	179 1/8 in. (4490 mm)	2 1/8 in. (57.2 mm)
1062	180 1/8 in. (4515 mm)	2 1/8 in. (57.2 mm)
1068	181 1/8 in. (4540 mm)	2 1/8 in. (57.2 mm)
1074	182 1/8 in. (4565 mm)	2 1/8 in. (57.2 mm)
1080	183 1/8 in. (4590 mm)	2 1/8 in. (57.2 mm)
1086	184 1/8 in. (4615 mm)	2 1/8 in. (57.2 mm)
1092	185 1/8 in. (4640 mm)	2 1/8 in. (57.2 mm)
1098	186 1/8 in. (4665 mm)	2 1/8 in. (57.2 mm)
1104	187 1/8 in. (4690 mm)	2 1/8 in. (57.2 mm)
1110	188 1/8 in. (4715 mm)	2 1/8 in. (57.2 mm)
1116	189 1/8 in. (4740 mm)	2 1/8 in. (57.2 mm)
1122	190 1/8 in. (4765 mm)	2 1/8 in. (57.2 mm)
1128	191 1/8 in. (4790 mm)	2 1/8 in. (57.2 mm)
1134	192 1/8 in. (4815 mm)	2 1/8 in. (57.2 mm)
1140	193 1/8 in. (4840 mm)	2 1/8 in. (57.2 mm)
1146	194 1/8 in. (4865 mm)	2 1/8 in. (57.2 mm)
1152	195 1/8 in. (4890 mm)	2 1/8 in. (57.2 mm)
1158	196 1/8 in. (4915 mm)	2 1/8 in. (57.2 mm)
1164	197 1/8 in. (4940 mm)	2 1/8 in. (57.2 mm)
1170	198 1/8 in. (4965 mm)	2 1/8 in. (57.2 mm)
1176	199 1/8 in. (4990 mm)	2 1/8 in. (57.2 mm)
1182	200 1/8 in. (5015 mm)	2 1/8 in. (57.2 mm)
1188	201 1/8 in. (5040 mm)	2 1/8 in. (57.2 mm)
1194	202 1/8 in. (5065 mm)	2 1/8 in. (57.2 mm)
1200	203 1/8 in. (5090 mm)	2 1/8 in. (57.2 mm)
1206	204 1/8 in. (5115 mm)	2 1/8 in. (57.2 mm)
1212	205 1/8 in. (5140 mm)	2 1/8 in. (57.2 mm)
1218	206 1/8 in. (5165 mm)	2 1/8 in. (57.2 mm)
1224	207 1/8 in. (5190 mm)	2 1/8 in. (57.2 mm)
1230	208 1/8 in. (5215 mm)	2 1/8 in. (57.2 mm)
1236	209 1/8 in. (5240 mm)	2 1/8 in. (57.2 mm)
1242	210 1/8 in. (5265 mm)	2 1/8 in. (57.2 mm)
1248	211 1/8 in. (5290 mm)	2 1/8 in. (57.2 mm)
1254	212 1/8 in. (5315 mm)	2 1/8 in. (57.2 mm)
1260	213 1/8 in. (5340 mm)	2 1/8 in. (57.2 mm)
1266	214 1/8 in. (5365 mm)	2 1/8 in. (57.2 mm)
1272	215 1/8 in. (5390 mm)	2 1/8 in. (57.2 mm)
1278	216 1/8 in. (5415 mm)	2 1/8 in. (57.2 mm)
1284	217 1/8 in. (5440 mm)	2 1/8 in. (57.2 mm)
1290	218 1/8 in. (5465 mm)	2 1/8 in. (57.2 mm)
1296	219 1/8 in. (5490 mm)	2 1/8 in. (57.2 mm)
1302	220 1/8 in. (5515 mm)	2 1/8 in. (57.2 mm)
1308	221 1/8 in. (5540 mm)	2 1/8 in. (57.2 mm)
1314	222 1/8 in. (5565 mm)	2 1/8 in. (57.2 mm)
1320	223 1/8 in. (5590 mm)	2 1/8 in. (57.2 mm)
1326	224 1/8 in. (5615 mm)	2 1/8 in. (57.2 mm)
1332	225 1/8 in. (5640 mm)	2 1/8 in. (57.2 mm)
1338	226 1/8 in. (5665 mm)	2 1/8 in. (57.2 mm)
1344	227 1/8 in. (5690 mm)	2 1/8 in. (57.2 mm)
1350	228 1/8 in. (5715 mm)	2 1/8 in. (57.2 mm)
1356	229 1/8 in. (5740 mm)	2 1/8 in. (57.2 mm)
1362	230 1/8 in. (5765 mm)	2 1/8 in. (57.2 mm)
1368	231 1/8 in. (5790 mm)	2 1/8 in. (57.2 mm)
1374	232 1/8 in. (5815 mm)	2 1/8 in. (57.2 mm)
1380	233 1/8 in. (5840 mm)	2 1/8 in. (57.2 mm)
1386	234 1/8 in. (5865 mm)	2 1/8 in. (57.2 mm)
1392	235 1/8 in. (5890 mm)	2 1/8 in. (57.2 mm)
1398	236 1/8 in. (5915 mm)	2 1/8 in. (57.2 mm)
1404	237 1/8 in. (5940 mm)	2 1/8 in. (57.2 mm)
1410	238 1/8 in. (5965 mm)	2 1/8 in. (57.2 mm)
1416	239 1/8 in. (5990 mm)	2 1/8 in. (57.2 mm)
1422	240 1/8 in. (6015 mm)	2 1/8 in. (57.2 mm)
1428	241 1/8 in. (6040 mm)	2 1/8 in. (57.2 mm)
1434	242 1/8 in. (6065 mm)	2 1/8 in. (57.2 mm)
1440	243 1/8 in. (6090 mm)	2 1/8 in. (57.2 mm)
1446	244 1/8 in. (6115 mm)	2 1/8 in. (57.2 mm)
1452	245 1/8 in. (6140 mm)	2 1/8 in. (57.2 mm)
1458	246 1/8 in. (6165 mm)	2 1/8 in. (57.2 mm)
1464	247 1/8 in. (6190 mm)	2 1/8 in. (57.2 mm)
1470	248 1/8 in. (6215 mm)	2 1/8 in. (57.2 mm)