

ANNUAL VEHICLE INSPECTION REPORT

VEHICLE HISTORY RECORD

REPORT NUMBER	FLEET UNIT NUMBER	DATE
640483935	601	02/16/24

MOTOR CARRIER OPERATOR

Liki TRANSPORTATION Inc dba B&Z

ADDRESS

8225 LECLAIRE AVE.

CITY, STATE, ZIP CODE

BURBANK, IL 60459

VEHICLE TYPE ☐ TRACTOR ☐ TRAILER ☒ TRUCK ☐ BUS
☐ (OTHER)

INSPECTOR'S NAME (PRINT OR TYPE)

Jugoslav Kovacevic

THIS INSPECTOR MEETS THE QUALIFICATION REQUIREMENTS IN SECTION 396.19.

☒ YES

VEHICLE IDENTIFICATION (✓ AND COMPLETE)

☐ LIC. PLATE NO. ☒ VIN ☐ OTHER 3AKJHHJ123PS041525

INSPECTION AGENCY/LOCATION (OPTIONAL)

VEHICLE COMPONENTS INSPECTED

OK	NEEDS REPAIR	REPAIRED DATE	ITEM	OK	NEEDS REPAIR	REPAIRED DATE	ITEM
✓			1. BRAKE SYSTEM	✓			e. Pitman Arm
✓			a. Service Brakes	✓			f. Power Steering
✓			b. Parking Brake System	✓			g. Ball and Socket Joints
✓			c. Brake Drums or Rotors	✓			h. Tie Rods and Drag Links
✓			d. Brake Hose	✓			i. Nuts
✓			e. Brake Tubing	✓			j. Steering System
			f. Low Pressure Warning Device				8. SUSPENSION
			g. Tractor Protection Valve				a. Axle Positioning Parts
			h. Air Compressor	✓			b. Spring Assembly
N/A			i. Electric Brakes	✓			c. Torque, Radius or Tracking Components
			j. Hydraulic Brakes				9. FRAME
✓			k. Vacuum Systems	✓			a. Frame Members
✓			l. Antilock Brake System	✓			b. Tire and Wheel Clearance
✓			m. Automatic Brake Adjusters	N/A			c. Adjustable Axle Assemblies (Sliding Subframes)
			2. COUPLING DEVICES				10. TIRES
✓			a. Fifth Wheels	✓			a. Steer-Axle Tires
			b. Pintle Hooks	✓			b. All Other Tires
N/A			c. Drawbar/Towbar Eye	N/A			c. Speed-Restricted Tires
✓			d. Drawbar/Towbar Tongue	N/A			11. WHEELS AND RIMS
✓			e. Safety Devices	N/A			a. Lock or Side Ring
✓			f. Saddle-Mounts	✓			b. Wheels and Rims
			3. EXHAUST SYSTEM	✓			c. Fasteners
✓			a. No leaks forward of/directly below the driver/sleeper compartment.	✓			d. Welds
N/A			b. Bus: No leaking/discharging in violation of standard.				12. WINDSHIELD GLAZING
✓			c. Unlikely to burn, char, or damage the electrical wiring, fuel supply, or any combustible part of vehicle.	✓			No cracks, discoloration, obstacles, etc. (see 393.60 for exceptions).
			4. FUEL SYSTEM	✓			13. WINDSHIELD WIPERS
✓			a. No visible leak.				Any power unit that has an inoperative wiper, or missing or damaged parts that render it ineffective.
✓			b. Fuel Tank Filler Cap	✓			14. MOTORCOACH SEATS
✓			c. Fuel tank securely attached.	✓			Any passenger seat that is not securely fastened to the vehicle structure.
			5. LIGHTING DEVICES				15. REAR IMPACT GUARD
✓			All lighting devices and reflectors required by Section 393 shall be operable.	N/A			In place, securely attached, proper size, proper placement (see 393.86).
			6. SAFE LOADING				16. OTHER
✓			a. Vehicle parts, load, dunnage, spare tire, etc., secured.				List any other condition(s) which may prevent safe operation of this vehicle.
N/A			b. Front End Structure				
N/A			c. Intermodal Container Securement Devices				
			7. STEERING MECHANISM				
✓			a. Steering Wheel Free Play				
✓			b. Steering Column				
✓			c. Front Axle Beam/All Other Steering Components				
✓			d. Steering Gear Box				

PASSINSTRUCTIONS: MARK COLUMN ENTRIES TO VERIFY INSPECTION: ☒ OK, ☒ NEEDS REPAIR, ☒ IF ITEMS DO NOT APPLY, ☐ REPAIRED DATE

CERTIFICATION: THIS VEHICLE HAS PASSED ALL THE INSPECTION ITEMS FOR THE ANNUAL VEHICLE INSPECTION IN ACCORDANCE WITH 49 CFR PART 396.

A vehicle does not pass an inspection if it has one of the following defects or deficiencies:

- Brake System.**
 - Service brakes.**—(1) Absence of braking action on any axle required to have brakes upon application of the service brakes (such as missing brakes or brake shoe(s) failing to move upon application of a wedge, S-cam, cam, or disc brake).

- (2) Missing or broken mechanical components including: shoes, lining, pads, springs, anchor pins, spiders, cam rollers, push-rods, and air chamber mounting bolts.

- (3) Loose brake components including air chambers, spiders, and cam shaft support brackets.

- (4) Audible air leak at brake chamber (Example—ruptured diaphragm, loose chamber clamp, etc.).

- (5) Readjustment limits. (a) The maximum pushrod stroke must not be greater than the values given in the tables below and at §393.47(e). Any brake stroke exceeding the readjustment limit will be rejected. Stroke must be measured with engine off and reservoir pressure of 80 to 90 psi with brakes fully applied.

CLAMP-TYPE BRAKE CHAMBERS

Type	Outside diameter	Brake readjustment limit—standard stroke chamber	Brake readjustment limit—long stroke chamber
6	4 1/8 in. (114 mm)	1 1/8 in. (31.8 mm)	
9	5 1/8 in. (133 mm)	1 1/8 in. (34.9 mm)	
12	5 7/8 in. (145 mm)	1 1/8 in. (34.9 mm)	1 1/8 in. (44.5 mm)
16	6 1/8 in. (162 mm)	1 1/8 in. (44.5 mm)	2 in. (50.8 mm)
20	6 7/8 in. (172 mm)	1 1/8 in. (44.5 mm)	2 in. (50.8 mm)
24	7 1/8 in. (184 mm)	1 1/8 in. (44.5 mm)	2 in. (50.8 mm)
30	8 1/8 in. (206 mm)	2 in. (50.8 mm)	2 1/8 in. (63.5 mm)
36	9 in. (229 mm)	2 1/8 in. (63.5 mm)	

¹ For type 20 chambers with a 3-inch (76 mm) rated stroke.
² For type 24 chambers with a 3-inch (76 mm) rated stroke.

BENDIX DD-3 BRAKE CHAMBERS

Type	Outside diameter	Brake readjustment limit
30	8 1/8 in. (206 mm)	2 1/8 in. (57.2 mm)

BOLT-TYPE BRAKE CHAMBERS

Type	Outside diameter	Brake readjustment limit
A	6 1/8 in. (176 mm)	1 1/8 in. (34.9 mm)
B	9 1/8 in. (234 mm)	1 1/8 in. (44.5 mm)
C	8 1/8 in. (205 mm)	1 1/8 in. (44.5 mm)
D	5 1/8 in. (133 mm)	1 1/8 in. (31.8 mm)
E	6 1/8 in. (157 mm)	1 1/8 in. (34.9 mm)
F	11 in. (279 mm)	2 1/8 in. (57.2 mm)
G	9 1/8 in. (251 mm)	2 in. (50.8 mm)

ROTOCHAMBER-TYPE BRAKE CHAMBERS

Type	Outside diameter	Brake readjustment limit
9	4 1/8 in. (109 mm)	1 1/8 in. (38.1 mm)
12	4 3/8 in. (122 mm)	1 1/8 in. (38.1 mm)
16	5 1/8 in. (138 mm)	2 in. (50.8 mm)
20	5 3/8 in. (151 mm)	2 in. (50.8 mm)
24	6 1/8 in. (163 mm)	2 in. (50.8 mm)
28	7 1/8 in. (180 mm)	2 1/8 in. (57.2 mm)
36	9 1/8 in. (194 mm)	2 1/8 in. (60.9 mm)
50	9 1/8 in. (226 mm)	3 in. (76.2 mm)

- (b) For actuator types not listed in these tables, the pushrod stroke must not be greater than 80 percent of this rated stroke marked on the actuator by the actuator manufacturer, or greater than the readjustment limit marked on the actuator by the actuator manufacturer.

- (c) Brake linings or pads.
 - Lining or pad is not firmly attached to the shoe;

- (d) Saturated with oil, grease, or brake fluid; or

- (e) Non-steering axles: Lining with a thickness less than 1/4 inch at the shoe center for air drum brakes, 1/16 inch or less at the shoe center for hydraulic and electric drum brakes, and less than 1/8 inch for air disc brakes.

- (f) Steering axles: Lining with a thickness less than 1/4 inch at the shoe center for drum brakes, less than 1/8 inch for air disc brakes and 1/16 inch or less for hydraulic disc and electric brakes.

- (g) Missing brake on any axle required to have brakes.

- (h) Mismatch across any power unit steering axle of:

- (a) Air chamber sizes.

- (b) Slack adjuster length.

Wedge Brake Data.—Movement of the scribe mark on the lining shall not exceed 1/16 inch.

- b. **Parking Brake System.** No brakes on the vehicle or combination are applied upon actuation of the parking brake control, including driveline hand controlled parking brakes.

- c. **Brake Drums or Rotors.**

- (1) With any external crack or cracks that open upon brake application (do not confuse short hairline heat check cracks with flexural cracks).

- (2) Any portion of the drum or rotor missing or in danger of falling away.

- d. **Brake Hose.**

- (1) Hose with any damage extending through the outer reinforcement ply. (Rubber impregnated fabric cover is not a reinforcement ply). (Thermoplastic nylon may have braid reinforcement or color difference between cover and inner tube. Exposure of second color is cause for rejection.)

- (2) Bulge or swelling when air pressure is applied.

- (3) Any audible leaks.

- (4) Two hoses improperly joined (such as a splice made by sliding the hose ends over a piece of tubing and clamping the hose to

the tube).

- (5) Air hose cracked, broken or crimped.

- e. **Brake Tubing.**

- (1) Any audible leak.

- (2) Tubing cracked, damaged by heat, broken or crimped.

- f. **Low Pressure Warning Device** missing, inoperative, or does not operate at 55 psi and below, or 1/2 the governor cut-out pressure, whichever is less.

- g. **Tractor Protection Valve.** Inoperative or missing tractor protect on valve(s) on power unit.

- h. **Air Compressor.**

- (1) Compressor drive belts in condition impending or probable failure.

- (2) Loose compressor mounting bolts.

- (3) Cracked, broken or loose pulley.

- (4) Cracked or broken mounting brackets, braces or adaptors.

- i. **Electric Brakes.**

- (1) Absence of braking action on any wheel required to have brakes.

- (2) Missing or inoperative breakaway braking device.

- j. **Hydraulic Brakes.** (Including Power Assist Over Hydraulic and Engine Drive Hydraulic Booster).

- (1) Master cylinder less than 1/4 full.

- (2) No pedal reserve with engine running except by pumping pedal.

- (3) Power assist unit fails to operate.

- (4) Seeping or swelling brake hose(s) under application of pressure.

- (5) Missing or inoperative check valve.

- (6) Has a visually observed leaking hydraulic fluid in the brake system.

- (7) Has hydraulic hose(s) abraded (chafed) through outer cover-to-fabric layer.

- (8) Fluid lines or connections leaking, restricted, crimped, cracked or broken.

- (9) Brake failure or low fluid warning light on and/or inoperative.

- k. **Vacuum Systems.** Any vacuum system which:

- (1) Has insufficient vacuum reserve to permit one full brake application after engine is shut off.

- (2) Has vacuum hose(s) or line(s) restricted, abraded (chafed) through outer cover to cord ply, crimped, cracked, broken or has collapse of vacuum hose(s) when vacuum is applied.

- (3) Lacks an operative low-vacuum warning device as required.

- l. **Antilock Brake System** ^{1,2,3}

- (1) Missing ABS malfunction indicator components (i.e., bulb, wiring, etc.).

- (2) ABS malfunction indicator that does not illuminate when power is first applied to the ABS controller (ECU) during initial power up.

- (3) ABS malfunction indicator that stays illuminated while power is continuously applied to the ABS controller (ECU).

- (4) ABS malfunction indicator lamp on a trailer or dolly does not cycle when electrical power is applied (a) only to the vehicle's constant ABS power circuit, or (b) only to the vehicle's stop lamp circuit.

- (5) With its brakes released and its ignition switch in the normal run position, power unit does not provide continuous electrical power to the ABS on any air-braked vehicle it is equipped to tow.

- (6) Other missing or inoperative ABS components.

- m. **Automatic Brake Adjusters**

- (1) Failure to maintain a brake within the brake stroke limit specified by the vehicle manufacturer.

- (2) Any automatic brake adjuster that has been replaced with a manual adjuster.

- (3) Damaged, loose, or missing components.

- (4) Any brake that is found to be out of adjustment on initial inspection must be evaluated to determine why the automatic brake adjuster is not functioning properly and the problem must be corrected in order for the vehicle to pass the inspection. It is not acceptable to manually adjust automatic brake adjusters without first correcting the underlying problem. For example, there may be other components within the braking system that are distressed or out of specification (i.e., broken welds, loose mounting hardware, cracked brake drums, worn bushings, etc.) that would require immediate attention.

2. **Coupling devices.**

- a. **Fifth Wheels.**

- (1) Mounting to frame.

- (a) Any fasteners missing or ineffective.

- (b) Any movement between mounting components.

- (c) Any mounting angle iron cracked or

1. Power units manufactured after March 1,

- 2001, have two ABS malfunction indicators, one for the power unit and one for the units that they tow. Both malfunction indicators are required to be fully functional.

2. Air-braked vehicles: Subsections (1)-(6) of this section are applicable to tractors with air brakes built on or after March 1, 1997, and all other vehicles with air brakes built on or after March 1, 1998.

3. Hydraulic-braked vehicles: Subsections (1)-(3) of this section are applicable to vehicles over 10,000 lbs. GVWR with hydraulic brakes built on or after September 1, 1999. Subsection (6) of this section is applicable to vehicles over 10,000 lbs. with hydraulic brakes built on or after March 1, 1999.

4. Fuel System.

- a. A fuel system with a visible leak at any point.

- b. A fuel tank filler cap missing.

- c. A fuel tank not securely attached to the motor vehicle by reason of loose, broken or missing mounting bolts or brackets (some fuel tanks use springs or rubber bushings to permit movement).

5. **Lighting Devices.** All lighting devices

- broken.

- (2) Mounting plates and pivot brackets.

- (a) Any fasteners missing or ineffective.

- (b) Any welds or parent metal cracked.

- (c) More than 3/8 inch horizontal movement between pivot bracket pin and bracket.

- (d) Pivot bracket pin missing or not secured.

- (e) Sliders.

- (a) Any latching fasteners missing or ineffective.

- (b) Any fore or aft stop missing or not securely attached.

- (c) Movement more than 3/8 inch between slider bracket and slider base.

- (d) Any slider component cracked in parent metal or weld.

- (e) Lower coupler.

- (a) Horizontal movement between the upper and lower fifth wheel halves exceeds 1/2 inch.

- (b) Operating handle not in closed or locked position.

- (c) Kingpin not properly engaged.

- (d) Separation between upper and lower coupler allowing light to show through from side to side.

- (e) Cracks in the fifth wheel plate.

- Exceptions: Cracks in fifth wheel approach ramps and casting shrinkage cracks in the ribs of the body of a cast fifth wheel.

- (f) Locking mechanism parts missing, broken, or deformed to the extent the kingpin is not securely held.

- b. **Pintle Hooks.**

- (1) Mounting to frame.

- (a) Any missing or ineffective fasteners (a fastener is not considered missing if there is an empty hole in the device but no corresponding hole in the frame or vice versa).

- (b) Mounting surface cracks extending from point of attachment (e.g., cracks in the frame at mounting bolt holes).

- (c) Loose mounting.

- (d) Frame cross member providing pintle hook attachment cracked.

- (e) Integrity.

- (a) Cracks anywhere in pintle hook assembly.

- (b) Any welded repairs to the pintle hook.

- (c) Any part of the horn section reduced by more than 20%.

- (d) Latch insecure.

- c. **Drawbar/Towbar Eye.**

- (1) Mounting.

- (a) Any cracks in attachment welds.

- (b) Any missing or ineffective fasteners.

- (c) Integrity.

- (a) Any cracks.

- (b) Any part of the eye reduced by more than 20%.

- d. **Drawbar/Towbar Tongue.**

- (1) Slider (power or manual).

- (a) Ineffective latching mechanism.

- (b) Missing or ineffective stop.

- (c) Movement of more than 1/4 inch between slider and housing.

- (d) Any leaking, air or hydraulic cylinders, hoses, or clambars (other than slight oil weeping normal with hydraulic seals).

- (e) Integrity.

- (a) Any cracks.

- (b) Movement of 1/4 inch between subframe and drawbar at point of attachment.

- e. **Safety Devices.**

- (1) Safety devices missing.

- (2) Unattached or incapable of secure attachment.

- (3) Chains and hooks.

- (a) Worn to the extent of a measurable reduction in link cross section.

- (b) Improper repairs including welding, wire, small bolts, rope and tape.

- (c) Cable.

- (a) Kinked or broken cable strands.

- (b) Improper clamps or clamping.

- f. **Saddle-Mounts.**

- (1) Method of attachment.

- (a) Any missing or ineffective fasteners.

- (b) Loose mountings.

- (c) Any cracks or breaks in a stress or load bearing member.

- (d) Horizontal movement between upper and lower saddle-mount halves exceeds 1/4 inch.

3. **Exhaust System.**

- a. Any exhaust system determined to be leaking at a point forward of or directly below the driver/sleeper compartment.

- b. A bus exhaust system leaking or discharging to the atmosphere:

- (1) Gasoline powered—excess of 6 inches forward of the rearmost part of the bus.

- (2) Other than gasoline powered—in excess of 15 inches forward of the rearmost part of the bus.

- (3) Other than gasoline powered—forward of a door or window designed to be opened. (exception: Emergency exits).

- c. No part of the exhaust system of any motor vehicle shall be so located as would be likely to result in burning, charring, or damaging the electrical wiring, the fuel supply, or any combustible part of the motor vehicle.

4. **Fuel System.**

- a. A fuel system with a visible leak at any point.

- b. A fuel tank filler cap missing.

- c. A fuel tank not securely attached to the motor vehicle by reason of loose, broken or missing mounting bolts or brackets (some fuel tanks use springs or rubber bushings to permit movement).

5. **Lighting Devices.** All lighting devices

broken.

- (2) Mounting plates and pivot brackets.

- (a) Any fasteners missing or ineffective.

- (b) Any welds or parent metal cracked.

- (c) More than 3/8 inch horizontal movement between pivot bracket pin and bracket.

- (d) Pivot bracket pin missing or not secured.

- (e) Sliders.

- (a) Any latching fasteners missing or ineffective.

- (b) Any fore or aft stop missing or not securely attached.

- (c) Movement more than 3/8 inch between slider bracket and slider base.

- (d) Any slider component cracked in parent metal or weld.

- (e) Lower coupler.

- (a) Horizontal movement between the upper and lower fifth wheel halves exceeds 1/2 inch.

- (b) Operating handle not in closed or locked position.

- (c) Kingpin not properly engaged.

- (d) Separation between upper and lower coupler allowing light to show through from side to side.

- (e) Cracks in the fifth wheel plate.

- Exceptions: Cracks in fifth wheel approach ramps and casting shrinkage cracks in the ribs of the body of a cast fifth wheel.

- (f) Locking mechanism parts missing, broken, or deformed to the extent the kingpin is not securely held.

- b. **Pintle Hooks.**

- (1) Mounting to frame.

<